

COMPACTCUT 300

LISSMAC
CONSTRUCTION TECHNOLOGY

THE ALL-ROUND FLOOR SAW FOR FAST AND EFFICIENT USE

- Lowering and raising the saw blade is done smoothly by means of an enclosed threaded spindle with cutting depth display, thereby preventing damage to the saw blade
- Spindle outside of the dirt area and protected by a galvanised teal tube
- Saw hood front can be raised for intersections
- Easily removable saw blade guard
- Standard with saw blade flange for multiple blade holder up to 15 mm
- A large 30 litre capacity water tank with a big filler nozzle and carrying handles makes refilling easier and reduces work interruptions
- Connection for external water supply with separately adjustable water tap
- Standard flange spraying saves water and provides optimum saw blade cooling. This guarantees a longer saw blade life.
- Water tank can be tipped forward – easy to refill, water tank can be completely emptied
- During cutting, more weight can be placed on the saw blade due to the tiltable tank
- Vibration-damping handle reduces the vibrations which can affect the user and improves the working conditions
- Handle is continuously adjustable and can be rotated 180° for an optimal straight cut
- Best transport option using crane lifting hook and handle
- Standard with fixing brake



Cyclonic pre-separator



Depth gauge with interlock



Incl. water tank – can be tilted forward



Vibration-damping handle



Saw hood front can be raised

TECHNICAL DATA	COMPACTCUT 300 P
cutting depth max.	180 mm
cutting depth setting	stepless threaded spindle with depth gauge
saw blade Ø max.	500 mm
arbor size	25.4 mm
drive motor	Honda petrol 1-cyl.
output power max.	8.7 kW, 11.8 hp
saw blade speed	2300 1/min.
dimensions (L/W/H)	1040/ 585 / 910 mm
weight	105 kg

DIAMOND TOOLS RECOMMENDATION

Asphalt	ASW 11
Concrete	BSW 12
Asphalt/Concrete	MUSW 10

FLOOR SAWS	NR.
COMPACTCUT 300 P without diamond blade, incl. blade guard 500 mm	1080762
TOOLS	NR.
ASW 11 diamond blade Ø 450 mm / 25,4 mm for asphalt	1054980
ASW 11 diamond blade Ø 500 mm / 25,4 mm for asphalt	1054982
BSW 12 diamond blade Ø 450 mm / 25,4 mm for concrete	1070155