

COMBI 250-1000 / 1500 VA

Water-cooled tile saws - blade Ø 250 mm

IDEAL FOR
LARGE TILES

Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor, 1.5 kW with thermal protection and minimum voltage coil
- ✓ IP 55 switch
- ✓ IP 67 plug
- ✓ Laser pointer
- ✓ Cutting guide
- ✓ Diamond blade Ø 250 mm PREMIUM for gres hard porcelain - continuous rim
- ✓ Protractor with large support surface
- ✓ Anodised extruded aluminium cutting surface
- ✓ Shatter-resistant plastic tray to contain and recover water
- ✓ Stand with two rubber wheels
- ✓ Side cutting surface (only for Combi 250-1500)

Optional Accessories and recommended blades

- ✓ Side cutting surface
- ✓ Tile locking tool
- ✓ Diamond blade Ø 250 mm FLEX for ceramic - continuous rim
- ✓ Diamond blade Ø 250 mm PREMIUM for gres hard porcelain - continuous rim

Applications

For a quality cut even on large tiles: 300x600 mm, 900x900 mm and over. Max. cutting length 1000 mm (Combi 250-1000) / 1500 mm (Combi 250-1500).

They offer high cutting capacity: the blade is suitable for all types of material to be cut. Cuts (90°) vertically to the support surface or cuts in tilted position between 90° and 45° (depth adjustment is maintained in all positions).

Side cutting surface allows to extend cutting, maintaining stability, due to a bracket bolted onto the stand. The machine can mount up to 2 side cutting surfaces and is shipped in a box with stand included.

115V/60Hz SPH

220V/60Hz SPH

MOTOR AVAILABLE

✓ Combi 250-1000 / 1500 VA

only 40 kg
without stand

only 47 kg
without stand



Tile locking tool



Handle for long cuts
(only Combi 250-1500)




Rip guide



Off button incorporated in the handle



Standard protractor



Cutting at 45°



Standard laser pointer



Combi 250-1500VA



Combi 250-1000VA

| | | COMBI 250-1000 VA | COMBI 250-1500 VA |
|---|-------|---------------------------|---------------------------|
| Blade/bore diameter | ø mm | 250/25.4 | 250/25.4 |
| Cutting length (with/without plunging blade 2 passes) | mm | 930/1030 | 1430/1530 |
| Cutting depth 1 pass | mm | 66 | 66 |
| Cutting depth 2 passes | mm | 105 | 105 |
| Cutting surface dimensions | mm | 500x1115 | 500x1615 |
| Motor power 230V/50Hz/absorption | kW/A | 1.5 / 9.4 | 1.5 / 9.4 |
| Motor speed | rpm | 2800 | 2800 |
| Water pump | - | IP 67, flow rate 13 l/min | IP 67, flow rate 13 l/min |
| Water recovery tray capacity | l | 40 | 55 |
| Machine dimensions | mm | 636/1420/619 | 636/1920/619 |
| Packing dimensions | mm | 669/1454/654 | 669/1954/654 |
| Stand dimensions | mm | 545/1060/750 | 545/1560/750 |
| Machine weight (with packing) | kg | 53 (65) | 75 (91) |
| Stand weight | kg | 16 | 17 |
| Optional surface weight (with packing) | kg | 6.2 (6.7) | 8.0 (8.6) |
| SPL in operator's position | dB(A) | 86 | 86 |