

# COMPACTCUT 201

# LISSMAC

CONSTRUCTION TECHNOLOGY

IDEALLY SUITED FOR SMALL AND MEDIUM SIZED REPAIR WORKS  
IN ASPHALT AND CONCRETE

- Floor saw in robust and compact construction
- The smooth raising and lowering of the saw blade with a closed threaded spindle prevents damaging of the saw blade
- Adjustable cutting depth indicator for all saw blade diameters
- A large water tank reduces work interruptions
- The water cooling system provides an optimum saw blade cooling, this guarantees a longer saw blade life
- Blade guard easily foldable
- Simple service operations - good access to engine and cutting shaft
- With a parking brake
- Height adjustable handles for ergonomic operation



COMPACTCUT 201 P



[ 1 ] COMPACTCUT 201 PL



[ 2 ] COMPACTCUT 201 PV



[ 3 ] COMPACTCUT 201 D



TECHNICAL DATA	COMPACTCUT 201 P	COMPACTCUT 201 PL	COMPACTCUT 201 PV
cutting depth max.	200 mm	200 mm	200 mm
cutting depth setting	stepless threaded spindle with depth gauge		
saw blade Ø max.	500 mm	500 mm	500 mm
arbor size	25.4 mm	25,4 mm	25.4 mm
drive motor	Honda petrol 1-cylinder	Loncin petrol 1-cylinder	Vanguard petrol 1-cylinder
output power max.	8.7 kW, 11.8 hp	8.2 kW / 11.1 hp	10.4 kW / 14 hp
saw blade speed	2500 1/min.	2500 1/min.	2400 1/min.
dimensions (L/W/H)	1195/620/1010 mm	1195/620/1010 mm	1195/620/1010 mm
weight	108 kg	108 kg	110 kg

TECHNICAL DATA	COMPACTCUT 201 D
cutting depth max.	200 mm
cutting depth setting	stepless threaded spindle with depth gauge
saw blade Ø max.	500 mm
arbor size	25,4 mm
drive motor	Kohler petrol 1-cylinder
output power max.	7.4 kW / 10 hp
saw blade speed	2700 1/min.
dimensions (L/W/H)	1195/620/1010 mm
weight	126 kg

#### DIAMOND TOOLS RECOMMENDATION

Asphalt	ASW 11
Concrete	BSW 12
Asphalt/Concrete	MUSW 10

FLOOR SAWS	NR.
COMPACTCUT 201 P without diamond blade, incl. blade guard 500 mm	1061483
[ 1 ] COMPACTCUT 201 PL without diamond blade, incl. blade guard 500 mm	1071322
[ 2 ] COMPACTCUT 201 PV without diamond blade, incl. blade guard 500 mm	1083554
[ 3 ] COMPACTCUT 201 D without diamond blade, incl. blade guard 500 mm	1079262

TOOLS	NR.
ASW 11 diamond blade Ø 450 mm / 25,4 mm for asphalt	1054980
ASW 11 diamond blade Ø 500 mm / 25,4 mm for asphalt	1054982
BSW 12 diamond blade Ø 450 mm / 25,4 mm for concrete	1070155