

CE

2  
YEARS  
WARRANTY**FS4043E****REBAR BENDING MACHINE**

singlephase	220V	50Hz/60Hz	3 kW [4 Hp]
	220V	60Hz	
threephase	440V	50Hz/60Hz	
	400V	50Hz/60Hz	

**DIMENSIONS**

Effective	cm 113 x 95 x H89
On Pallet*	cm 113 x 95 x H104**

\* standard packing with cardboard, protective film and plastic strips  
\*\* INDICATIVE PACKING

**WEIGHT**

Effective	kg 486
On Pallet*	kg 516**

SAE 40  
kg 13

6 rpm

**BENDING CAPACITY**R. = 65 Kg. / mm<sup>2</sup>R. = 85 Kg. / mm<sup>2</sup>

1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø
38	30	24	36	28	22

ALL TECHNICAL DATAS ARE SUBJECT TO CHANGE WITHOUT NOTICE DUE TO TECHNICAL IMPROVEMENTS

**STANDARD EQUIPMENT****Turning plate Ø460mm**

Bushes up to Ø260mm  
Ø336mm in case of BIG RADIUS EQUIPMENT




7 bushes Ø 50 - 60 - 70 - 80 - 95 - 120 - 150 mm , 1 hardened square pin; 1 hardened stirrup bending pin; 3 hardened bush holding pins; 1 checking block; 1 pedal for remote control;

**Long saddles**

Essentials for double bending

**OPTIONALS****Spiral equipment**

A device that allows you to fabricate rebar spiral, using bars up to Ø 16mm.




**Bench with rollers****2 speed motor**

Ideal solution to optimize the production time

ONLY 3-PHASE

**"2INI" stirrup bender and linear measurer**

It allows to know the lenght of the stirrups starting from the point of bending and to bend together more bars with the highest precision.

**Big radius equipment****20 ANGLES Control Panel****6 ANGLES Control Panel**

ONLY 3-PHASE

**FEAL-SEAM S.r.l.**

Via dell'Isola, 1/a

23900 Lecco (LC) - Italy

info@feal-seam.it

www.rebar-machines.com