

Standard Equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Self-braking motor with magnetic device
- ✓ Bracket can be extended up to 1120 mm
- ✓ Hoist protection cover

Optional Accessories

- ✓ Scaffold attachment
- ✓ 3-pushbutton IP65 pendant control 1.5 m
- ✓ 3-pushbutton IP65 pendant control 5 m
- ✓ 3-pushbutton IP65 pendant control 30 m - low voltage

Applications

The low noise level allows working without causing noise harmful to the operator's health and bothersome to others.

Telescopic frame 720 mm - 1120 mm



200 kg



19 m/min



30 m



TR 225 NEO

Maximum capacity	kg	200
Av. full load lifting speed	m/min	19
Max. working height	m	30
Ø steel rope	mm	4
Rope length	m	31
Electric power supply	V / Hz	230 / 50 Sph 110 / 50 Sph
Motor power rate	kW	0.75
Motor speed	rpm	1380
Running current 230 V (110 V)	A	7.2 (14)
Machine weight	kg	46
SPL in operator's position	db(A)	<70
Dimensions w/l closed (open)/h	mm	330/770(1170)/520
Packing dimensions w/l/h	mm	390/810/590