LMK 220

EASE OF OPERATION WHEN MOVING SMALL-SIZED ELEMENTS

- Base frame, tower and jig are completely galvanised
  – no rust or damage to paint
  – long service life and robustness for the toughest conditions
- Flexibly used
- Can be completely dismantled into individual parts
- Quick and easy to set up on site
- Suitable for 230 V mains, can be used anywhere
- Fast assembly/disassembly
- Easy transport by 2 people
- Powerful chain hoist
- Easy positioning with swivel castors
- Space efficient footprint



TECHNICAL DATA	LMK 220
lifting capacity	220 kg
hook height	4000 mm
weight without ballast	880 kg
ballast	400 kg
wheelbase	1900 / 1900 mm
turning radius	3500 mm
lifting speed	3-13 m/min
assy. and dismantling	hydraulic (hand pump)
voltage	230 V / 50 Hz
transport size (L/W/H)	5000 / 2000 / 2000 mm

Subject to technical change without notice
LISSMAC / 04.2024



Folded



Dismanteled into individual parts

MINI CRANES	NR.
LMK 220 – 230V/50Hz	1091411

ACCESSORIES	
Adapter for connection RSG - SG	821141
Adapter for connection VSG - outer gripper	820079

Gripping devices see page 80